




Radian™ Series

GS8048 Inverter/Charger

- **Grid-Interactive and Stand-Alone Capability in the Same Package**
- **8000 Watts of Continuous Power**
- **Unsurpassed Surge Capacity**
- **120/240V Split-Phase Voltage**
- **Dual AC Inputs**
- **Field Upgradeable Firmware**
- **Field Serviceable Modular Design**
- **Simplified Parallel Design Allows Easy Installation of Systems from 8 to 80kW**
- **GS Load Center Option Allows for Quick and Easy Installation**



The Radian Series GS8048 Grid/Hybrid™ (fully-flexible grid-interactive/off-grid) inverter/charger is engineered from the ground up making system design and installation easier and faster. A fully-integrated solution, the Radian delivers 8,000 Watts of pure sinewave continuous power with unsurpassed surge capacity to start the most demanding appliances. The Radian Series simplifies the configuration, distribution, and implementation of energy storage through a standardized approach when integrated with an OutBack GS load center, demonstrating OutBack Power's commitment to delivering clean, reliable power to homes, businesses and other facilities.

The Grid/Hybrid Radian incorporates OutBack's FLEXgrid™ technology for full operation flexibility. The Radian's Dual AC Inputs automatically switch between an active grid and generator input without the need for costly external transfer switch. In areas where the ability to sell energy back to the grid may be restricted or limited, the Radian's offset function enables users to manage their energy consumption by switching between PV, grid and battery energy sources and "off-setting" their dependence on the grid. Advanced technology allows the Radian to seamlessly manage

power from multiple sources and direct battery functions at the same time.

A unique dual-power module design ensures high efficiency in both low and full power operation as well as redundancy in both low and full power operation as well as redundancy in mission-critical applications. The Radian's modular system architecture and simplified parallel design supports system scaling of up to ten inverters delivering 80kW.

The 120/240V 60Hz split-phase Radian is an 8,000 Watt power solution that seamlessly integrates with traditional North American wiring practices. System integration and programming is easier with OutBack's MATE3 and HUB Communications Management devices. Advanced front-vented layout provides optimum cooling in zero-clearance installations. A field-serviceable design simplifies maintenance and firmware updates without the addition of specialized equipment.

OutBack
POWER™
member of The  Group™

www.outbackpower.com

Radian Series Specifications

		GS8048
Nominal DC Input Voltage		48 VDC
Continuous Output Power at 25°C		8000 VA
AC Output Voltage / Frequency		120/240 VAC / 60 Hz
Continuous AC Output Current at 25°C		33.3 Amps AC at 240 VAC
Idle Consumption - Invert mode, no load		30 W
Typical Efficiency		93%
CEC Weighted Efficiency		90%
Total Harmonic Distortion	Maximum total harmonic	<5%
	Maximum single voltage harmonic	<2%
Output Voltage Regulation		± 2%
Maximum Output Current	1 ms peak	100 Amps AC at 240 VAC, 200 Amps AC at 120 VAC
	100 ms RMS	70.7 Amps AC at 240 VAC
Overload Capability	100 ms surge	16.97 kVa
	5 seconds	12 kVa
	30 minute	9 kVa
AC Input Voltage Range (Adjustable)		(L1 or L2) 70 to 140 VAC
AC Input Frequency Range		54 to 66 Hz
Grid-Interactive Voltage Range (IEEE)		(L1 or L2) 108 to 132 VAC (IEEE)
Grid-Interactive Frequency Range (IEEE)		(L1 or L2) 59.3 to 60.5 Hz (IEEE)
Maximum AC Input Current		50 Amps AC at 240 VAC
Continuous Battery Charge Output		115 Amps DC
DC Input Voltage Range		40 to 64 VDC
Temperature Range	Rated	0 to 50°C (power derated above 25°C)
	Maximum	-25 to 60°C (Functions, but does not necessary meet all components specifications)
Accessory Ports		Remote Temperature Sensor and MATE3/HUB Communications
Non-volatile Memory		Yes
Field Upgradable Firmware		Yes
Chassis Type		Vented
Certifications		ETL Listed to UL1741, CSA C22.2 No. 107.1
Warranty		Standard 5 year Warranty
Weight	Unit	125 lbs (56.7 kg)
	Shipping	140 lbs (63.5 kg)
Dimensions (H x W x D)	Unit	28 x 16 x 8.7" (71.1 x 40.6 x 22.1 cm)
	Shipping	14.5 x 34.5 x 21" (36.8 x 87.6 x 53.3 cm)

Available From:

REMATEK-Energie
 514-333-6414
info@rematek-energie.com
www.rematek-energie.com



Corporate Office:
 5917 195th St. NE
 Arlington, WA 98223 USA
 Phone: +1 360 435 6030
 Fax: +1 360 435 6019

European Office:
 Hansastrasse 8
 D-91126
 Schwabach, Germany
 Phone: +49 9122 79889 0
 Fax: +49 9122 79889 21

Asia Office:
 Suite 1903, Tower 1, China Hong Kong City
 33 Canton Road, Kowloon
 Hong Kong
 Phone: +852 2736 8663
 Fax: +852 2199 7988

Latin American Office:
 15105 Cedar Bluff Pl.
 Wellington, FL 33414 USA
 Phone: +1 561 792 9651
 Fax: +1 561 792 7157